



UL 1015 Hook Up Wire

Application:

UL 1015, UL Style 1015 may be used for the internal wiring of appliances.

UL 1015, UL Style 1015 may be used for the internal wiring of appliances where exposed to oil at a temperature not exceeding 60 C or 80 C.

Description:

- Stranded Tinned Copper, Color Coded
- Polyvinylchloride Insulation, .032 nominal
- Temperature Range: -40°C to +105°C
- Voltage Rating: 600 Volts

Welcome your inquire and order! Email me: sales@kt-elec.com

Specifications:

AWG SIZE	Conductor	Stranded	NOM O.D. (Inches)	UL STYLE
26	Solid		0.08	1015/1230
26	7/34		0.083	1015/1230
24	Solid		0.084	1015/1230
24	7/32		0.089	1015/1230
22	Solid		0.09	1015/1230
22	7/30		0.095	1015/1230
20	Solid		0.095	1015/1230
20	10/30		0.102	1015/1230
18	Solid		0.106	1015/1230
18	16/30		0.112	1015/1230
16	Solid		0.115	1015/1230
16	26/30		0.125	1015/1230
14	Solid		0.128	1015/1230
14	41/30		0.14	1015/1230
12	Solid		0.145	1015/1230
12	65/30		0.163	1015/1230
10	65/28		0.18	1015/1230
10	105/30		0.194	1015/1230